

Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Series 786

· Article number: Series 786

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Printing inks

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Deco Technology Group, Inc.

Printcolor Screen AG Tel.: (714) 639-3326 Fax: (714) 639-2261

· Further information obtainable from: Product safety department

· 1.4 Emergency telephone number: (800) 535-5053

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P280 Wear protective gloves / eye protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

Contains 4-isocyanatosulphonyltoluene. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 2)



Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

· **vPvB:** Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 54839-24-6 EINECS: 259-370-9	2-ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black substance with a Community workplace exposure limit	1-2.5%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate The Flam. Liq. 3, H226; STOT SE 3, H336	1-2.5%
CAS: 34590-94-8 EINECS: 252-104-2	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	1-2.5%
CAS: 112-07-2 EINECS: 203-933-3	2-butoxyethyl acetate Output Description: Description: Output Description: Output	1-2.5%
CAS: 4083-64-1 EINECS: 223-810-8	4-isocyanatosulphonyltoluene ♦ Resp. Sens. 1, H334; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	< 1%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)



Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

(Contd. of page 2)

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

1333-86-4 Carbon black

WEL | Short-term value: 7 mg/m³

Long-term value: 3.5 mg/m³

123-86-4 n-butyl acetate

WEL | Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

34590-94-8 (2-methoxymethylethoxy)propanol

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

112-07-2 2-butoxyethyl acetate

WEL | Short-term value: 332 mg/m³, 50 ppm

Long-term value: 133 mg/m³, 20 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- · Protection of hands:





Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: $> 140 \, ^{\circ}\text{C}$

· Flash point: 44 °C (Abel Pensky)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 315 °C

• **Decomposition temperature:** Not determined.

· **Self-igniting**: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol % **Upper:** 10.8 Vol %

· Vapour pressure at 20 °C: 3.4 hPa

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.

(Contd. on page 5)



Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

(Contd. of page 4)

• **Evaporation rate** Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined. **VOC (EC)** 16.64 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

GB



Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

(Contd. of page 5)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue 08 03 12: waste ink containing dangerous substances
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information			
· 14.1 UN-Number · ADR, ADN · IMDG, IATA	Void UN1210		
· 14.2 UN proper shipping name · ADR, ADN · IMDG, IATA	Void PRINTING INK		
· 14.3 Transport hazard class(es)			
· ADR · Class · ADN/R Class:	Void Not restricted goods according to ADR 2.2.3.1.5 - shipped in containers less than 450L Void		
· IMDG, IATA			
& A STATE OF THE S			
· Class · Label	3 Flammable liquids.3		
· 14.4 Packing group · ADR · IMDG, IATA	Void III		
· 14.5 Environmental hazards: · Marine pollutant:	No		
· 14.6 Special precautions for user · EMS Number:	Not applicable. F-E,S-D		
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.			
· Transport/Additional information:			
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
· UN "Model Regulation":	-		



Printing date 29.04.2015 Version number 1 Revision: 29.04.2015

Trade name: Series 786

(Contd. of page 6)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing MSDS: Product safety department

· Contact:

hse@printcolor.ch

Martin Otto

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3