According to 91/155/EWG **Series 10-02637**

Date of issue / revised : 26-01-2006 Page 1 of 4

No.: 00918/RG/e

1.	IDENTIFICATION OF SUBSTANCE, PREPARATION AND COMPANY						
	TRADE NA		SERIE 10-02637				
	INTENDED USE		RETARDER				
	MANUFACTURER		Printcolor Screen LTD. Deco Technology Group TEL 714-639-3326 FAX 714-639-2261				
	EMERGENCY INFO	RMATION	TELEPHONE NUMBER 800-535-5053				
2.	Compositio	COMPOSITION / INFORMATION ON INGREDIENTS					
	2.1 CHEMICAL CHARACTERISTICS OF PRODUCT: MIXTURE OF SOLVENTS						
	2.2 SUBSTANCES PRESENTING A HEALTH HAZARD WITHIN THE MEANING OF GUIDE-LINES NO.67/548/EC OR ASSIGNED OCCUPATIONAL EXPOSURE LIMITS						
	CAS-No		ON ACCORDING TO EC GUIDE-LINES	CONCENTRATION WEIGHT-%	DANGERSYMBOL LETTER	R-PHRASES (*)	
	Mixture	Dimethyle	ster	> 95			
	(*) CLEAR TEXT O	F R-PHRASE	S SEE SECTION 15	1			
3.	HAZARDS IDI	ENTIFICA	TION				
	Danger Sign Special Danger Advice FOR Persons and Environment						
4.	FIRST AID M	EASURES	5				
	GENERAL In all cases of doubt or if symptoms persist, take medical advice. Never give anythin by mouth to an unconscious person; call a physician. Immediately remove all contaminated clothing.				ver give anything		
	INHALATION Remove to fresh air, keep the patient warm and at rest. If breath administer artificial respiration. Give nothing ba mouth. If unconscirecovery position and seek medical advice.						
	SKIN CONTACT Remove contaminated clothing. Wash skin thoroughly with soap and water or use proprietary skincleaner. DO NOT USE SOLVENTS OR THINNER.					d water or use a	
	EYE CONTACT		Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.				
	INGESTION		If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.				
5.	FIRE FIGHTIN	IG MEAS	URES				
	EXTINGUISHING I	EXTINGUISHING MEDIA					
	RECOMMENDED Alcohol resistant foam, CO ₂ , powder, water spray/mist						
	EXTINGUISHING MEDIA NOT SUITABLE Waterjet						
	SPECIAL PROTEC	CTION	Appropiate breathing apparatus may be required				
	RECOMMENDATION	Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighthing to enter drains or water courses.					

SDS/EGSI01/03-99/DH page 1

According to 91/155/EWG Series 10-02637

Date of issue / revised : 26-01-2006 Page 2 of 4

No.: 00918/RG/e

Date c	of issue / revised	: 26-01-	2006	Pa	ge 2 of 4		
6.	ACCIDENTAL RELEASE MEASURES						
	PERSONAL PRECEDURES PRECAUTIONS		Exclude sources of ignition and ventilate to Avoid breathing vapours. Refer to protective Do not allow to enter drains or water course and drains or soil, inform the responsible loc	e measures listed in Sections 7 and es. If the product contaminates rive	.8 b		
METHODS FOR CLEANING C			Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (see Section 13).				
7.	HANDLING AND STORAGE						
	HANDLING						
Prevent the creation of flammable or explosive concentrations of vavoid vapour concentrations exceeding the occupational exposure the product should only be used in areas which have been cleared from and other sources of ignition. The product may charge itself electro-state equipment should be protected properly. When pouring the procontainers, only ground mains should be used. It is recommended to clothing and foot wear. Use spark-proof tools. Avoid any contact was Smoking, eating and drinking should be prohibited in areas of storal personal protection see Section 8. Follow legal protective and safety in					Moreover, light, fire Electrical nto other antistatic s or skin. use. For		
	PROTECTION AGAINST EXPLOSIONS AND FIRES Vapours are heavier than air and may spread along floors. They may form mixtures in combination with air. Preparations may charge electrostatically: All earthing leads when transferring from one container to another.						
	STORAGE						
	REQUIREMENTS FOR STORAGE ROOMS AND CONTAINERS		Keep container tightly closed. Never use pressure to empty: Container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. No ressurized container.				
	ADVICE FOR COMBINED STORAGE		Store seperately from strong acid and alkaline materials as well as from oxidizing agents.				
	FURTHER ADVICE FOR STORAGE Store at a cool and well ventilated place. Avoid heating and direct sunlight. from flammable matters and observe instructions on the labels. Alway containers of same material as the original one.						
8.	EXPOSURE C	ONTROL	/ Personel Protection				
	ENGINEERING N	IEASURES					
	Provide adequate ventilation. Where reasonably practicable this should be achieved by use of local exhaust ventilation and good general extration. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn. (See 'Personal protection' below).						
		COMPONENTS WITH CRITICAL VALUES THAT REQUIRE MONITORING AT THE WORKPLACE (EXPOSURE LIMITS)					
i	CAS-No.	DESIGN	ATION ACCORDING TO EC GUIDE-LINES	OCCUPATIONAL EXPOSURE LIMITS	UNIT		
	The above values have been taken from the valid list (f.e.TRGS 900) of the Federal Republic of Germany or from the Regula SUVA/Switzerland regarding occupational exposure limits.				ulations of		

SDS/EGSI01/03-99/DH page 2

According to 91/155/EWG Series 10-02637

Date of issue / revised : Page 3 of 4 26-01-2006

No.: 00918/RG/e

	PERSONAL PROTECTION	N			
	RESPIRATORY PROTECTION	If the solvent vapor concentration exceed the exposure limits, the use of breathin apparatus is practical or necessary (breathing protection measures)			
	SKIN PROTECTION	Use protective gloves, e.g. Neoprene. At lasting or repeated contact of the product with the skin, use protecting emulsions. Observe recommendations of the manufacturer. After washing hands replace lost skin fat by fat containing skin creams Safety glasses as protection against splashes of solvents should be worn.			
	EYE PROTECTION				
	BODY PROTECTION	Cotton or cotton/synthetic overalls or coveralls are normally suitable. Personal should wear antistatic clothing's made of natural fiber or of high temperature resistant synthetic fiber. All parts of body should be washed after contact.			
9.	PHYSICAL AND CHEMICAL PROPERTIES				
	Form Color Odour	liquid transparent like solvents			
	Boiling point Flash point	Value Unit Method > 195 °C > 350 °C			
	Viscosity Density	app.2 mPas (23°C) 1,09 g/cm³ (23°C)			
	pH-Value Content of solvent Explosion limit	app. 7 1:1 in water 100 Weight-% Lower 0,8 Upper 8,5 Vol% (solvent)			
	Solubility in water	miscible at 23 °C			
10.	STABILITY AND REACTIVITY				
	STABILITY Stable under the recommended storage and handling conditions (see Section 7). Keep away from oxidizing agents and strongly alkaline and strongly acids prevent the possibility of exothermic reaction.				
	DANGEROUS PRODUCTS OF DECOMPOSITION	In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produce.			
11.	TOXICOLOGICAL IN	FORMATION			
	There is no data available on the product itself. It is formulated within the SBPIM's guidelines on materials for exclusion from printing inks and varnishes. Exposure to organic solvent vapors may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the rental and central nervous systems. Symptoms include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.				
12.	ECOLOGICAL INFO	RMATION			
	There is no data available on the product itself. The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.				

DISPOSAL CONSIDERATIONS 13.

WASTE KEYS	VeVAS-code	070704	Country	Switzerland
	Waste key (acc.TA-Abfall)	070704	Country	EC

PACKAGING The container and packaging materials are recyclable according to the local prescriptions and

regulations

DO NOT ALLOW INTO DRAINS OR WATER COURSES OR DISPOSE OF WHERE GROUND OR SURFACE WATERS MAY BE AFFECTED. WASTES, INCLUDING EMPTIED CONTAINERS, ARE CONTROLLED WASTES AND SHOULD BE DISPOSED OF IN ACCORDANCE WITH REGULATIONS MADE UNDER THE CONTROL OF POLLUTION ACT AND THE ENVIRONMENTAL PROTECTION ACT.

SDS/EGSI01/03-99/DH page 3

According to 91/155/EWG Series 10-02637

Date of issue / revised : 26-01-2006

14. TRANSPORT INFORMATIONS

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage. Transport only according to the transport regulations for road (ADR), rail (RID), sea (IMDG) and air (ICAO/IATA).

LAND TRANSPORT ADR/RID + GGVS/GGVE MARITIME TRANSPORT IMDG/GGVSEA

NOT RESTRICTED!!

AIR TRANSPORT ICAO/IATA

REGULATORY INFORMATION 15.

CLASSIFICATION ACCORDING TO EEC DIRECTIVES

DANGER SYMBOL n.a. **DANGER DESIGNATION** n.a. **HAZARD DETERMINING COMPONENTS OF LABELLING**

R-PHRASES

S-PHRASES 20/21 When using do not eat, drink or smoke

CLASSIFICATION ACCORDING TO BAG (SWITZERLAND) AND GERMAN DIRECTIVES

CH-SZID See also label % LUFTREINHALTEVERORDNUNG LRV-class % 2 % 100 1 3 % **IMMISSIONSSCHUTZ TA-Luft** % Ш Ш 100 % **VbF-class** Ш **BRANDSCHUTZ BVD-class**

WASSERHAUSHALT WGK (self-assessment) **CH** 3 **BRD**

THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET DOES NOT CONSTITUTE THE USER'S OWN ASSESSMENT OF WORKPLACE RISKS AS REQUIRED BY OTHER HEALTH AND SAFETY LEGISLATIONS. THE PROVISION OF THE HEALTH AND SAFETY AT WORK ETC. ACT AND THE CONTROL SUBSTANCES HAZARDOUS TO HEALTH REGULATIONS APPLY TO THE USE OF THIS PRODUCT AT

OTHER INFORMATIONS 16.

THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET IS PROVIDED IN ACCORDANCE WITH THE REQUIREMENTS OF THE CHIP REGULATIONS. THE PRODUCT SHOULD NOT BE USED FOR PURPOSES OTHER THAN THOSE SHOWN IN SECTION 1 WITHOUT FIRST REFERRING TO THE SUPPLIER AND OBTAINING WRITTEN HANDLING INSTRUCTIONS. AS THE SPECIFIC CONDITIONS OF USE OF THE PRODUCT ARE OUTSIDE THE SUPPLIER'S CONTROL, THE USER IS RESPONSIBLE FOR ENSURING THAT THE REQUIREMENTS OF RELEVANT LEGISLATION ARE COMPLIED WITH. THE INFORMATION CONTAINED IN THIS SAFETY DATA SHEET IS BASED ON THE PRESENT STATE OF KNOWLEDGE AND CURRENT NATIONAL LEGISLATION. IT PROVIDES GUIDANCE ON HEALTH, SAFETY AND ENVIRONMENTAL ASPECTS OF THE PRODUCT AND SHOULD NOT BE CONSTRUED AS ANY GUARANTEE OF TECHNICAL PERFORMANCE OR SUITABILITY FOR PARTICULAR APPLICATIONS

SDS/EGSI01/03-99/DH page 4

Page 4 of 4

No.: 00918/RG/e